



PIA-W-25361
18 October 2005

Renamed from
MIL-W-25361E
09 April 1990

The following commercial specification is adopted from the military document. Initial and Revision A included in all known accepted revisions, amendments, notices, and Department of Defense (DoD) engineering changes previously developed for this item. Revision B and later include changes adopted by DoD and Industry to reflect technology and design evolution.

Note: Although many military quality and inspection specifications, drawings and standards have been discontinued or deleted, most have been replaced by industry and commercial documents. When the specification refers to a discontinued or deleted document, you should refer to the procurement document or your contracting officer for guidance.

WEBBING, TEXTILE, POLYESTER, LOW ELONGATION

The Parachute Industry Association makes this document available for use by Industry and Government organizations that wish to apply this specification to their products.

1. SCOPE

1.1 Scope. This specification covers low elongation textile webbing composed of a continuous filament polyester warp and bulked nylon filling or a continuous filament polyester filling.

1.2 Classification. The webbing shall be of the following types and classes as specified (see 6.2).

Type:

- I - 3600-pound breaking strength
- II - 6000-pound breaking strength
- III - 7000-pound breaking strength
- IV - 8700-pound breaking strength
- V - 10,000 pound breaking strength
- VI - 15,000-pound breaking strength

DISTRIBUTION STATEMENT: All Rights Reserved. No Part of this publication may be reproduced without prior written permission from Parachute Industry Association. Additional copies may be purchased on-line from the PIA Store at: www.pia.com.

Copyright Protected: Do Not Copy!