



EJECTOR SNAP ASSEMBLY

WITH LEADING EDGE OF LEVER ARM GRIP RESTING ON THE PROJECTING BALL A LOAD OF 20 POUNDS MAX. SHALL BE APPLIED TO THE END OF THE LEVER ARM. (INSIDE HOOK MOUTH) THE GRIP SHALL CLOSE AND LOCK OVER THE BALL DETENT. (M2)

THE BAR WITH A 20 POUND WEIGHT APPLIED SHALL BE COMPLETELY EJECTED WHEN A MANUAL PULL (NOT EXCEEDING 15 POUNDS) IS APPLIED TO OPEN THE LEVER ARM TO FULL RELEASE POSITION. (C3)

(C4) SNAP SHALL ACCEPT A 9/32 DIA TEST BAR

RELEASE OF LEVER ARM FROM THIS POSITION SHALL CLOSE AND SEAT LEVER ARM GRIP OVER BALL DETENT. (M3)

(C5) LEVER ARM SHALL ROTATE TO ITS FULLY REJECTED POSITION (AGAINST DOUBLE TORSION SPRING BUSHING) WITHOUT RESISTANCE FROM DOUBLE TORSION SPRING.

Parachute Industry Association



3833 West Oakton St.
Skokie, IL 60076 USA
Tel (847) 674-9742
Fax (847) 674-9743
Web Address: pia.com

Title

SNAP, PARACHUTE HARNESS
QUICK-FIT EJECTOR

Parachute
Standard

PS22018

Procurement Specification
MIL-H-7195

Adopted From:
MS22018 (E)

Sheet 1 of 12