



DASH NO.	A	B	C	D	E	F	WT LBS	SUPERSEDES
-1	5/8	1/2	1/4	1/8	1/2	1/32	.007	48A7995
-2	11/16	1/2	1/4	1/8	1/2	1/16	.011	48A7995-1
-3	7/8	5/8	5/16	5/32	1/2	3/32	.023	48A7995-2
-4	5/8	1/2	1/4	1/8	1/2	1/32	.007	48A7995-3
-5	5/8	1/2	1/4	1/8	1/2	1/32	.007	----

NOTES:

- MATERIAL FOR -1 THRU -4: STEEL ASTM A-108, B1113 OR 1118 OR TUBE STEEL, ASTM A-513 AND ASTM A-519, 1118 CONDITION HR. MATERIAL FOR -5: STEEL MIL-S-5626 (4140) HEAT TREAT MIL-H-6875, 150,000 PSI MIN. (ROCKWELL C34-38)
- FINISH -1, -2, -3, & -5: CADMIUM PLATE, QQ-P-416, TYPE I, CLASS 1. DASH FOUR NICKEL PLATE, QQ-N-290, TYPE I, CLASS 1, FOLLOWED BY CHROMIUM PLATE, QQ-C-320, CLASS 1, TYPE I.
- $\sqrt{63}$ ALL OVER. SURFACE ROUGHNESS IN ACCORDANCE WITH ANSI 46.1.
- DIMENSIONS SHALL BE IN INCHES UNLESS OTHERWISE SPECIFIED. TOLERANCES: FRACTIONS $\pm 1/64$.
- FOR DESIGN PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.
- REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.
- ALTERNATE MATERIAL FOR -5: 41L40 PER FED-STD-66.

ADAPTED 1/7/98. REVISED (A) 4/29/04.

Parachute Industry Association



3833 West Oakton St.
Skokie, IL 60076 USA
Tel (847) 674-9742
Fax (847) 674-9743
Web Address: pia.com

Title

RING-REEFING
PARACHUTE

Parachute
Standard

PS27762

Procurement Specification
MIL-H-7195

Adopted From:
MS27762 (C)

Sheet 1 of 1