



NOTES:

1. MATERIAL: STEEL CORROSION-RESISTING FORM 1, CONDITION B PER QQ-W-423, EXCEPT TENSILE STRENGTH MAY BE 220,000, PSI MINIMUM.
2. REMOVE ALL BURRS AND SHARP EDGES ON ENDS OF WIRE.
3. THE WAVY BASE MUST BE PARALLEL WITH THE SHOULDERS AND SQUARE WITH HOOK WITHIN .015.
4. WHEN HOOK IS OPEN, THE END AND EYE SHALL BE AT LEAST .250 APART.
5. HOOK SHALL BE SUBJECTED TO A PROOF LOAD OF 25 LBS. IN THE DIRECTION INDICATED BY THE ARROWS. A 3/4 INCH WIDE WEBBING OR SUITABLE SUBSTITUTE SHALL BE USED TO DISTRIBUTE THE LOAD ACROSS THE WIDTH OF THE WAVY BASE. WHEN PROOF LOAD IS APPLIED, THE WAVY BASE MAY DEFLECT BUT SHALL NOT DISENGAGE EYE.
6. DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS $\pm .015$, ANGLES $\pm 2^\circ$.

FOR DESIGN FEATURE PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN.

REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATION FOR BID.

REVISED (A) 4/28/2005

Parachute Industry Association



3833 West Oakton St.
Skokie, IL 60076 USA
Tel (847) 674-9742
Fax (847) 674-9743
Web Address: pia.com

Title

**HOOK, BAND, PARACHUTE
CONTAINER OPENING**

**Parachute
Standard**

PS90295

Procurement Specification

Adopted From:

MS90295 (A)

Sheet 1 of 1